

Mode	Nominal pressure (kN)	Max. bending width (mm)	Distance between uprights (mm)	Throat depth (mm)	Cylinder stroke (mm)	Opening height (mm)	Main power (kW)	Total power (kW)	Speed (mm/s)			Dimensions (mm)			Weight (kg)
									Approaching speed	Working speed	Returning speed	Length	Width	Height	
BDE5016	500	1600	1200	250	160	460	4	9	180	0-10	160	2160	1245	2205	3000
BDE6325	630	2500	2100	350	160	460	5.5	10.5	180	0-10	160	3040	1385	2450	4300
BDE8025	800	2500	2100	350	160	465	7.5	12.5	180	0-10	160	3040	1385	2450	5000
BDE8032	800	3200	2600	350	160	465	7.5	12.5	180	0-10	160	3740	1385	2450	6000
BDE10025	1000	2500	2100	400	200	480	7.5	12.5	180	0-10	160	3060	1595	2600	6300
BDE10032	1000	3200	2600	400	200	480	7.5	12.5	180	0-10	160	3700	1595	2650	6600
BDE10042	1000	4200	3600	400	200	480	7.5	12.5	180	0-10	160	4800	1595	2650	8300
BDE13032	1300	3200	2600	400	200	480	11	16	180	0-10	160	3720	1575	2650	6800
BDE13042	1300	4200	3600	400	200	480	11	16	180	0-10	160	4820	1575	2650	8500
BDE17032	1700	3200	2600	400	200	480	11	16	180	0-10	160	3720	1650	2730	8400
BDE17042	1700	4200	3600	400	200	480	11	16	180	0-10	160	4820	1650	2730	9800
BDE17050	1700	5000	4000	400	200	480	11	16	180	0-10	160	5600	1800	2960	13800
BDE17060	1700	6000	5000	400	200	480	15	20	180	0-10	160	6630	1800	3160	16500
BDE20032	2000	3200	2600	400	200	480	15	20	180	0-10	160	3740	1695	2870	9650
BDE20042	2000	4200	3400	400	200	480	15	20	180	0-10	160	4740	1695	2870	11500
BDE20050	2000	5000	4000	400	200	480	15	20	180	0-10	160	5630	1850	3100	15000
BDE20060	2000	6000	5000	400	200	480	18.5	23.5	180	0-10	160	6630	1850	3210	17500
BDE25032	2500	3200	2600	400	250	500	18.5	23.5	160	0-8	120	3760	1700	3015	12000
BDE25042	2500	4200	3400	400	250	500	18.5	23.5	160	0-8	120	4760	1700	3015	14800
BDE25050	2500	5000	4000	400	250	500	18.5	23.5	160	0-8	120	5650	1920	3125	17800
BDE25060	2500	6000	5000	400	250	500	22	28	160	0-8	120	6650	1920	3325	20500
BDE32032	3200	3200	2600	500	250	500	22	28	160	0-8	120	3780	1800	3375	14600
BDE32042	3200	4200	3400	500	250	500	22	28	160	0-8	120	4780	1800	3375	18000
BDE32050	3200	5000	4000	500	250	500	22	28	140	0-8	110	5830	2150	3690	23500
BDE32060	3200	6000	5000	500	250	500	22	28	140	0-8	110	6830	2150	3855	27800
BDE40032	4000	3200	2600	500	300	600	30	36	110	0-8	110	3460	2350	3600	25700
BDE40042	4000	4200	3400	500	300	600	30	36	110	0-8	110	4360	2350	3600	28500
BDE40050	4000	5000	4000	500	300	600	30	36	100	0-8	100	5260	2350	4700	34700
BDE40060	4000	6000	5000	500	300	600	30	36	100	0-8	100	6260	2350	5000	40000
BDE50032	5000	3200	2600	500	300	600	37	43	90	0-7	90	3480	2580	4600	33000
BDE50042	5000	4200	3400	500	300	600	37	43	90	0-7	90	4360	2580	4700	37000
BDE50050	5000	5000	4000	500	300	600	37	43	90	0-7	90	5260	2580	4900	42000
BDE50060	5000	6000	5000	500	300	600	37	43	90	0-7	90	6260	2580	5200	47000
BDE60042	6000	4200	3400	550	300	600	45	51	90	0-7	90	4360	3530	4950	46000
BDE60050	6000	5000	4000	550	300	600	45	51	90	0-7	90	5260	3530	5050	52000
BDE60060	6000	6000	5000	550	300	600	45	51	90	0-7	90	6260	3530	5200	59000

